






Boiler SUBMITTAL DATA SHEET




Top View



Front View



Back View



Right Side View

2 Appliances can be stacked vertically with included bracket kit



PO BOX 3244 | LANCASTER, PA 17601

AMP-1250 C

Appliance Certified for use as Boiler or DHW

INNOVATIVE EQUIPMENT FOR
HOT WATER SYSTEMS

WWW.THERMALSOLUTIONS.COM

Updated 12/10/2025

ABC-251201



Boiler SUBMITTAL DATA SHEET

RATINGS AND CAPACITIES		
Input - Low fire:	125,000	BTU/HR
Input - High Fire:	1,250,000	BTU/HR
Output - High Fire:	1,212,000	BTU/HR
Boiler Horsepower:	36	BHP
Recovery Rate:	1,485	GPH
Thermal / Combustion Efficiency %:	97	
Heating Surface:	99	Sq.Ft.
Water Vol. (gal):	11	Gallons
Fuel:	Natural Gas ONLY	
Firing Rate:	Full Modulation	
Burner Turndown:	10:1	
Low NOx Emissions:	<20 ppm	
Inlet Gas Pressure (NG):	4" (Min.) / 14" (Max.)	
Inlet Gas Pressure (LP):	Natural Gas ONLY	
Approx. Shipping Weight (lb):	770	lbs.

ASME Section IV (Max 160 PSIG / 210°F)

Setpoint range is 60-185°F

Adjustable, manual reset high limit setting of ≤ 200°F.

ASME H stamp MAWT is 210°F for the vessel. (For max setpoint, see Setpoint range.)

ETL Certified to ANSI Z21.13 / CSA 4.9 & ANSI Z21.10.3 / CSA/4.3

ETL Certified to UL 795 / CSA 3.1 & NSF / ANSI Standard 372



FLOWS AND PRESSURE DROPS		
Delta T	Flow (GPM)	Head Loss (ft)
20°	121	24.5
30°	81	11.5
40°	61	6.7

Electrical Requirements: (Appliance Only)				
Model	Voltage	Phase	Hz	Max. Amp Draw
400	120	1	60	7
500				7
650				8
800				8
1000				8
1250-1500				10

BOILER ALTERNATIVE RELIEF VALVE KITS (75 PSI STD.)			
<input type="checkbox"/>	30 PSI	<input type="checkbox"/>	100 PSI
<input type="checkbox"/>	50 PSI	<input type="checkbox"/>	125 PSI
<input type="checkbox"/>	60 PSI	<input type="checkbox"/>	150 PSI

Water Heater T&P Relief Valve Kits		
<input type="checkbox"/>	125 PSI	
<input type="checkbox"/>	150 PSI	

NOTES:
1. Height dimension is from floor to top of jacket.
2. Length is from jacket front to jacket rear.
3. Dimensions shown are for reference only
4. Refer to manual for gas supply piping charts

DIMENSIONS / CONNECTIONS		
Height:	40 1/4	(Note 1)
Width:	26 3/8	(Note 2)
Length:	55 3/8	(Note 3)
Water Outlet Pipe (FNPT):	2	
Water Inlet Pipe (MNPT):	2	
Vent Connection:	8	
Air Intake Connection:	6	
Condensate Drain (PVC):	1	
Drain Line Connection:	3/4	
Gas Inlet Connection (FPT):	1-1/4	



Boiler SUBMITTAL DATA SHEET

STANDARD EQUIPMENT

PRESSURE VESSEL DESIGN

Stainless Steel Heat Exchanger

ASME Section IV Certified, "H" Stamp

MAWP 160 PSIG & Max Temp 210°F

Setpoint range is 60-185°F

Adjustable, manual reset high limit setting of ≤ 200°F.

ASME H stamp MAWT is 210°F for the vessel. (For max setpoint, see Setpoint range.)

Ten Year Limited Pressure Vessel Warranty

COMBUSTION DESIGN

Stainless Steel Pre-Mix Burner

Low NOx Emissions (< 20 ppm)

Full Modulation, 10:1 Turndown

Natural Gas ONLY

4-14" wc inlet natural gas pressure

Direct Spark Ignition System

High/Low gas pressure switches, manual reset

Variable Speed Combustion Blower

Blocked Vent Switch

VENTING

Category II or IV Venting

Individual or Common (Engineered) Vent System

Vertical or Horizontal

8" Stainless Steel Vent Connection

NOTE: Optional 8" PVC Vent adapter, PN# 113404-01 available.

Direct Vent & Sealed or Room Air or Outdoor Ready

Outdoor installations require the optional outdoor exhaust vent kit

APPLIANCE EQUIPMENT

Indoor / Outdoor Construction (Field Convertible)

Stainless steel water piping suitable for boiler or domestic (potable) water applications

Concert™ Control (24 Vac)

High Limit Temp Control, Manual Reset

Low water cutoff, manual reset

Water Flow Switch

Supply & Return Water Temperature Sensors

Flue Gas Temperature Sensor

Condensate trap

Blocked Condensate Switch

Pressure & Temperature Gauge

ASME 75 PSI Relief Valve Standard (Available 30, 50, 60, 100, 125 or 150 psig)

NOTE: Stacking Brace Kit (PN# 111405-00 included with all 400-1500 models. Kit includes 2 braces & 8 self-drilling screws.

NOTE: For stacking outdoor boilers, consult factory

ELECTRICAL DESIGN

Models 400-500

-120 VAC Only

AMP Draw: 7.0 Amps

Models 650-1000

-120 VAC Only

AMP Draw: 8.0 Amps

Models 1250-1500:

-120 VAC Only

AMP Draw: 10.0 Amps

24VAC/5VDC - Low Voltage PCB

- EMS Communications

(Dual RJ45 Jacks for Peer-To-Peer or Modbus)

- Boiler Options (Sensors)

- Pumps (Boiler, DHW, System) & Auxiliary Devices

* Flue system material shall be capable of continuous operation at 210°F or higher and shall be certified to UL 1738 – venting system for gas-burning appliances cat II, III and IV.



Boiler SUBMITTAL DATA SHEET

OPTIONAL EQUIPMENT

- Hydronic Kit (Boiler Circulation Pump, Pump Flange Kit and Condensate Neutralizer)
- Water Heater Pump (Circulation Pump & Pump Flange Kit)
- External High Limit Temperature Control, Manual Reset
- Condensate Neutralizer
- Supply Header Temperature Sensor:
- Outdoor Air Temperature Sensor (Wired)
- Domestic Hot Water Sensor with Well Kit
- EMS Signal Converter Kit (Converts Energy or Building Management System 0-10v signal to 4-20mA)
- Alarm Buzzer with Silencing Switch
- CPVC Adapter Kit, 8" (1250 & 1500) PN#112308-01
- PVC /CPVC Vent Kit PN# 111569-01, Sizes 400-500
- Outdoor Vent Kit PN# 110644-01, Sizes 400-500
- Universal Communications Gateway
- Conductor Sequencing Panel
- 4-12 GPG Water Hardness
- 12-15 GPG Water Hardness
- Direct Immersion
- Well Immersion (with Well)
- PN# 111569-02, Sizes 650-1000
- PN# 110645-01, Sizes 650-1000
- BACnet, Metasys N2,Modbus
- Optional Isolation Relay Board
- PN# 113404-01, Sizes 1250-1500
- PN# 113442-01, Sizes 1250-1500 (8")
- LonWorks

The Conductor manages multiple condensing & non-condensing, small & large heat output, new and/or existing boilers (full modulation or on-off), and steam or hot water applications. It helps improve system efficiency by selecting and modulating the right boiler to match operating conditions. The Conductor offers a single point boiler plant Energy Management System (EMS) interface including Modbus TCP/IP, Modbus RTU RS485, BACnet/IP and BACnet MSTP standard. If LonWorks needed, add for the separate LonWorks gateway.

- Water Heater Storage Tank

Model: _____ Size: _____

EXTENDED WARRANTY

- 3-Year Parts
- 5-Year Parts
- 10-Year Parts
- 5-Year Parts/Labor
- 10-Year Parts/Labor



Boiler SUBMITTAL DATA SHEET

CONCERT CONTROL FEATURES



Dashboard - Color Touchscreen Display, 4"

Intuitive Icon Navigation

"Quick" Setup Menus

*Real Time BTU/H Display

Two (2) Temperature Demand Inputs

Outdoor Air Reset Curve for Each Input

Time of Day Setback Capability

(Enviracom Thermostat must be installed)

Three (3) Pump Control

Boiler Pump With On/Off or Variable Speed Control

Domestic Hot Water (DHW) Pump

System Pump

Alternative Control to Combustion

Air Damper or Standby Loss Damper

Pump Overrun for Heat Dissipation

Pump Exercise

Pump Rotor Seizing Protection

Peer-to-Peer Boiler Communications

Multiple Size Boiler Sequencing Up to 8 Units

*Two (2) Boiler Start/Stop Trigger

Lead Boiler Automatic Rotation

Energy Management System (EMS) Interface

*Firing Rate and Water Temperature Based

Algorithms for Multiple Boilers; loss of EMS signal defaults to local boiler settings

420mA Input/Output (010Vdc Optional Converter)

ModBus Input/Output (BACnet or LonWorks Optional Gateway)

Simultaneous Interface with Peer-to-Peer

USB Data Port Transfer

Upload Settings Between Boilers

Download Parameters for Troubleshooting

Import Data into .CRV Formatted Files for Performance Analysis

* Unique to Concert

Energy Efficiency Enhancer

Anticycling Technology

Multiple Boiler base load common rate

Outdoor Air Temperature Reset Curve

Warm Weather Shutdown

Boost Temperature & Time

Ramp Delay

Overtemperature Safeguarding

Self-Guiding Diagnostics

Identifies Fault

Describes Possible Problems

Provides Corrective Actions

Time/Date Stamp on Alarms and Lockouts

Unmatched Archives

Historical Trends Collects Up to 4 months Data

Event History Up to 3000 Alarms, Lockouts and Cycle & Run Times

Alarm Limit String Faults, Holds, Lockouts and Others

Cycle & Run Time Boilers & Pumps

Resettable (Lockouts/Alarms/Cycles & Run Time)

Domestic Hot Water Priority

DHW Tank Piped With Priority in the Boiler Loop

DHW Tank Piped as a Zone in the System With the Pumps Controlled by the Concert Control

DHW Modulation Limiting

Status Screens

Sensor Monitoring and Control

Other Features

Factory Default Settings

Three Level Password Security

Frost Protection

Contractor Contacts (Up to 3)

Low Water Flow Safety Control & Identification


Proportional Integral Derivative (PID) Parameters for Central Heat, DHS, Sequencer and Fan

Boiler Connect Compatible

Requires one (1) Boiler Connect Bluetooth Adapter Kit (PN#113329-01) per install or cascade)



Boiler SUBMITTAL DATA SHEET



BOILER Connect

BOILER CONNECT FEATURES

Bluetooth adapter connects to the Boiler Connect App

English or Spanish language

Start-up, Troubleshooting Tips and Service Wizards

Data logs, Service and Status Reports sent to the cloud

Live Data Sharing (Cellular Service Required) with Technical Service Representative