Innovative Solutions for Heating and Domestic Hot Water Systems





Thermal Solutions is an industry-leading manufacturer of commercial and industrial hydronic products including high efficiency condensing boilers, near-condensing boilers, and hot water heaters. Our product line features reliable and easy-to-maintain products backed by decades of engineering expertise and product development, but the most important thing is your job and your specifications. Thermal Solutions has the people and products to provide a solution that fits your needs.



Condensing Boilers & Water Heaters









- 97% thermal efficiency (b)
- 98% thermal efficiency 6
- 10:1 turndown ratio


- 3-in-1 vent connector
- · Stackable no rack required
- · Outdoor-rated models available
- · Concert control with color touch screen display











- 97% thermal efficiency (b)
- 98% thermal efficiency 6
- 5:1 turndown ratio

- 300' equivalent intake and exhaust
- Knockdown configuration
- Outdoor-rated model available
- · Concert control with color touch screen display




Arctic 6



- 95% thermal efficiency
- 5:1 turndown ratio (1,000-3,000 MBH)
- 20:1 turndown ratio (3,500-6,000 MBH)
- Exclusive field-repairable heat exchanger - only condensing boiler
- Optional knockdown configuration
- · Concert control with color touch screen display





- Up to 97% thermal efficiency
- 5:1 turndown ratio

- 3-in-1 vent connector
- Stackable no rack required
- Concert control with color touch screen display



Non-Condensing Boilers & Water Heaters









- 8 models from 500 MBTUH to 3.0 MBTUH (
- 4 models from 750 MBTUH to 3.0 MBTUH
- Up to 87% thermal efficiency (
- Up to 82% thermal efficiency 6
- 3:1 turndown ratio
- Maximum setpoint 230°F (, 200°F ()
- Bronze headers 6
- Thick and durable copper tubes
- · Outdoor-rated models available (EVS)
- Thermal Solutions Boiler Control (TSBC) available (EVS)



H₂O Max

- . 2.5x the output of traditional stainless indirects
- · Hot water heat exchanger
- · Corrosion-free tank design
- 4 sizes
- Up to 30 GPM instantaneous DHW delivery
- 10-year limited warranty



Additional Accessories

- · Circulating pumps
- · Air separators
- · Hydraulic separators
- · Magnetic filters
- · Heat exchangers
- Storage tanks
- · Expansion tanks
- Buffer tanks
- · Hot water generators





Conductor Hydronic Sequencer

- Simple integration of boiler plants; hybrid, electric, hydronic heat pump, condensing, non-condensing, hot water, or steam
- · System pump rotation
- Customizable operating parameters
- · Works with non-Thermal Solutions branded products

Product Performance



THERMAL EFFICIENCY	INPUT CAPACI	TY							
98%	Water Heater: 399-3999 CAT II and IV								
97%	Boiler: 399-3999 CAT II and IV								









EVOLUTION



85%		Во	ilers: 500)-3000	CAT	II and	IV				
82%		Wa	ter Heate	rs: 750	-3000	CAT	II and	ı IV			
	400	1000	160	10	2200 Units		2800 n in MI		3400	4000	6000



